

BEAST SERIES / CERTIFIED INSTALLERS

BEAST PRO

NL-TDS-BEAST-PRO-EN | REV 1.0 | DOCUMENT DATE 26 SEP 2026

ENGLISH EDITION / PRODUCT TECHNICAL INFORMATION

A professional single-layer quartz coating developed for high gloss and a slick clear-coat finish.

Intended surfaces: Automotive clear coat.

01 / TECHNICAL DATA

Pack size	50 mL
System role	Single-layer coating
Tack-free	1 h
Initial cure	12 h
First wash	After 14 days
Full cure	30 days
Warranty	5 years; conditions apply
Appearance [2]	Clear, colourless liquid

Values are from the product information [1]; entries marked [2] are from the referenced SDS. Values are not batch acceptance limits.

04 / STORAGE & SHELF LIFE

Store at 0-25°C in the tightly closed original container. Shelf life: at least 12 months; use within 180 days after opening.

05 / APPLICATION NOTES & SAFE USE

Application by NANOLAB certified installers only. Warranty coverage is subject to the applicable installation and maintenance conditions.

For technical parameters not specified in this document and substrate-specific advice, contact NANOLAB technical support.

Read the current product-specific SDS and label before use. Follow their ventilation, PPE, handling and disposal instructions. This sheet does not replace the SDS.

[1] Product information: www.nanolab.ltd/beast-pro/

[2] Linked SDS, section 9: [NANOLAB-BEAST-PRO-US-SDS-03122023.pdf](#)

Reference information accessed 26 Sep 2026. Use together with the current product label and SDS.

02 / APPLICATION

01 Certified NANOLAB installers only. Work in small sections in a cool, low-humidity, air-conditioned area, away from direct wind.

02 Polish as appropriate, then remove oil and residue with PREP.

03 Prime an applicator and spread evenly in crossing passes.

04 Wait for haze or rainbowing; remove excess with one microfiber towel and finish with a second.

03 / CARE & MAINTENANCE

Wash with pH-neutral shampoo, dry and inspect; refresh with suitable maintenance coating. Certified-installer service every 6-12 months is a warranty condition.