

BEAST SERIES / CLEAR COAT

BEAST

NL-TDS-BEAST-EN | REV 1.0 | DOCUMENT DATE 26 SEP 2026

ENGLISH EDITION / PRODUCT TECHNICAL INFORMATION

A single-layer quartz ceramic coating designed to enhance gloss and surface slickness.

Intended surfaces: Automotive clear coat.

01 / TECHNICAL DATA

Pack size	50 mL
System role	Single-layer coating
Tack-free	1 h
Initial cure	12-24 h*
First wash	After 14 days
Full cure	30 days
Warranty	3 years; conditions apply
Appearance [2]	Clear, colourless liquid

Values are from the product information [1]; entries marked [2] are from the referenced SDS. Values are not batch acceptance limits.

04 / STORAGE & SHELF LIFE

Store at 0-25°C in the tightly closed original container. Shelf life: at least 12 months; use within 180 days after opening.

05 / APPLICATION NOTES & SAFE USE

*Initial curing is weather-dependent. Warranty coverage is subject to the applicable installation and maintenance conditions.

For technical parameters not specified in this document and substrate-specific advice, contact NANOLAB technical support.

Read the current product-specific SDS and label before use. Follow their ventilation, PPE, handling and disposal instructions. This sheet does not replace the SDS.

[1] Product information: www.nanolab.ltd/beat/

[2] Linked SDS, section 9: [NANOLAB-BEAST-US-SDS-01252021.pdf](#)

Reference information accessed 26 Sep 2026. Use together with the current product label and SDS.

02 / APPLICATION

01 Polish as appropriate, then remove oil and residue with PREP.

02 Prime an applicator and spread evenly in crossing passes.

03 Wait for haze or rainbowing; remove excess with one microfiber towel and finish with a second.

03 / CARE & MAINTENANCE

Wash with pH-neutral shampoo, dry and inspect; refresh with suitable maintenance coating. Certified-installer service every 6-12 months is a warranty condition.