

SURFACE PROTECTION / GLOSSY FILMS

GLOSS

NL-TDS-GLOSS-EN | REV 1.0 | DOCUMENT DATE 26 SEP 2026

ENGLISH EDITION / PRODUCT TECHNICAL INFORMATION

A single-layer ceramic coating for glossy films, combining gloss enhancement, slickness and hydrophobic surface behaviour.

Intended surfaces: Glossy paint protection film (PPF) and glossy vinyl wraps.

01 / TECHNICAL DATA

Pack size	50 mL
Application build	1 layer
Tack-free	2 h
Initial cure	24 h
First wash	After 14 days
Full cure	30 days
Warranty	1 year; conditions apply
Appearance [2]	Clear, colourless liquid

Values are from the product information [1]; entries marked [2] are from the referenced SDS. Values are not batch acceptance limits.

04 / STORAGE & SHELF LIFE

Store at 0-25°C in the tightly closed original container. Shelf life: at least 12 months; use within 180 days after opening.

05 / APPLICATION NOTES & SAFE USE

Confirm compatibility with the installed film and its care instructions. Warranty coverage is subject to the applicable maintenance conditions.

For technical parameters not specified in this document and substrate-specific advice, contact NANOLAB technical support.

Read the current product-specific SDS and label before use. Follow their ventilation, PPE, handling and disposal instructions. This sheet does not replace the SDS.

[1] Product information: www.nanolab.ltd/gloss/

[2] Linked SDS, section 9: [NANOLAB-GLOSS-US-SDS-03152024.pdf](#)

Reference information accessed 26 Sep 2026. Use together with the current product label and SDS.

02 / APPLICATION

01 Remove oils and residue with PREP.

02 Prime an applicator; spread evenly with crossing passes.

03 Wait for haze or rainbowing. Remove excess with one microfiber towel; finish with a second.

03 / CARE & MAINTENANCE

Use pH-neutral shampoo, dry and inspect. Certified-installer maintenance and GLOSS reapplication every 6 months are specified for warranty validity.