

SURFACE PROTECTION / MATTE FINISHES

MATTE

NL-TDS-MATTE-EN | REV 1.0 | DOCUMENT DATE 26 SEP 2026

ENGLISH EDITION / PRODUCT TECHNICAL INFORMATION

A single-layer ceramic coating providing slickness and water repellency while preserving the intended matte/satin appearance.

Intended surfaces: Matte clear coat, matte PPF and matte vinyl wraps.

01 / TECHNICAL DATA

Pack size	50 mL
Application build	1 layer
Tack-free	30 min
Initial cure	12-24 h; weather-dependent
First wash	After 14 days
Full cure	30 days
Warranty	1 year; conditions apply
Appearance [2]	Clear, colourless liquid

Values are from the product information [1]; entries marked [2] are from the referenced SDS. Values are not batch acceptance limits.

04 / STORAGE & SHELF LIFE

Store at 0-25°C in the tightly closed original container. Shelf life: at least 12 months; use within 180 days after opening.

05 / APPLICATION NOTES & SAFE USE

Do not polish matte surfaces. The visual wipe-off cue does not indicate full cure. Warranty coverage is subject to the applicable maintenance conditions.

For technical parameters not specified in this document and substrate-specific advice, contact NANOLAB technical support.

Read the current product-specific SDS and label before use. Follow their ventilation, PPE, handling and disposal instructions. This sheet does not replace the SDS.

[1] Product information: www.nanolab.ltd/matte/

[2] Linked SDS, section 9: [NANOLAB-MATTE-US-SDS-03152024.pdf](#)

Reference information accessed 26 Sep 2026. Use together with the current product label and SDS.

02 / APPLICATION

01 Clean with PREP. Do not polish matte surfaces.

02 Prime an applicator; coat each complete part systematically.

03 Wait for the described sweat-like marks. Level with a microfiber towel, then turn it to finish.

03 / CARE & MAINTENANCE

Wash with pH-neutral shampoo, dry and inspect. Certified-installer service and MATTE reapplication every 6 months are specified for warranty validity.