

SURFACE PROTECTION / PLASTIC & RUBBER

PLASTIC

NL-TDS-PLASTIC-EN | REV 1.0 | DOCUMENT DATE 26 SEP 2026

ENGLISH EDITION / PRODUCT TECHNICAL INFORMATION

A flexible ceramic coating designed for water repellency and protection against UV exposure, weathering and wear.

Intended surfaces: Unpainted interior and exterior plastic and rubber surfaces.

01 / TECHNICAL DATA

Pack size	50 mL
Tack-free	30 min
Initial cure	12-24 h; weather-dependent
First wash	After 14 days
Full cure	30 days
Appearance [2]	Clear, colourless liquid

Values are from the product information [1]; entries marked [2] are from the referenced SDS. Values are not batch acceptance limits.

04 / STORAGE & SHELF LIFE

Store at 0-25°C in the tightly closed original container. Shelf life: at least 12 months; use within 180 days after opening.

05 / APPLICATION NOTES & SAFE USE

Confirm compatibility with the specific plastic or rubber grade and surface finish.

For technical parameters not specified in this document and substrate-specific advice, contact NANOLAB technical support.

Read the current product-specific SDS and label before use. Follow their ventilation, PPE, handling and disposal instructions. This sheet does not replace the SDS.

[1] Product information: www.nanolab.ltd/plastic/

[2] Linked SDS, section 9: [NANOLAB-PLASTIC-US-SDS-01202021.pdf](#)

Reference information accessed 26 Sep 2026. Use together with the current product label and SDS.

02 / APPLICATION

01 Clean using PREP, a suitable all-purpose cleaner or plastic cleaner.

02 Spread with a primed applicator using crossing passes.

03 Allow absorption, then remove excess with microfiber. Turn the towel and finish evenly.

03 / CARE & MAINTENANCE

Clean with a suitable cleaner and reapply as required.