

WASH & CARE / POLYMERIC SPRAY

RECOAT

NL-TDS-RECOAT-EN | REV 1.0 | DOCUMENT DATE 26 SEP 2026

ENGLISH EDITION / PRODUCT TECHNICAL INFORMATION

A polymeric spray treatment designed to improve gloss, slickness and water repellency as a standalone coating, top coat or maintenance product.

Intended surfaces: Top-coat, maintenance and standalone use; confirm the target substrate/system.

01 / TECHNICAL DATA

Pack size	473 mL / 16 fl oz
Product type	Polymeric spray coating
Application method	Microfiber wipe and buff
System roles	Standalone / top coat / care
Cure / wash interval	Not specified
Coverage / dilution	Not specified

Technical values refer to the product information [1]. Where stated, curing and working times are typical guidance and depend on conditions.

04 / STORAGE & SHELF LIFE

Store at 0-25°C in the tightly closed original container. Shelf life: at least 12 months; use within 180 days after opening.

05 / APPLICATION NOTES & SAFE USE

Confirm compatibility with the existing coating system and any required waiting period before subsequent treatments.

For technical parameters not specified in this document and substrate-specific advice, contact NANOLAB technical support.

Read the current product-specific SDS and label before use. Follow their ventilation, PPE, handling and disposal instructions. This sheet does not replace the SDS.

[1] Product information: www.nanolab.ltd/recoat/

Reference information accessed 26 Sep 2026. Use together with the current product label and SDS.

02 / APPLICATION

01 Wash the surface.

02 Spray product onto a microfiber towel and distribute.

03 Turn the towel or use a second towel to buff and remove excess.

03 / CARE & MAINTENANCE

Reapply as needed.